

Technic data sheet:

VCT CLEAN

The **GREEN** alternative for Vinyl Composition Tile Floors

PRODUCT DESCRIPTION: isi GmbH Germany ECOGUARD™ VCT Clean offers all of the advantages of high grade commercial cleaners and stripping compounds in a 100% Green solution. ECOGUARD Daily Cleaner is organically enhanced soy-based which provides an excellent medium to emulsify multiple layers of hardened wax or coatings, residual glue, and remove stubborn deep stains from resilient flooring surfaces.

ECOGUARD VCT Clean is designed to work with the isi's Patented VCT Diamond abrasive pads to remove existing wax/coatings on vinyl flooring and to deep cleanse and remove surface scratches, as well as embedded glue in seams. The combination of VCT Clean with the VCT Diamond pads rejuvenates any vinyl composition resilient flooring to like-new condition with bright and deep colors as it was on the originally installed tiles or sheets. The floor becomes easier to maintain, retaining a maximum gloss with periodical high speed burnishing using the VCT Daily Maintenance pad, in conjunction with the ECOGUARD VCT Shield and Daily Cleaner.

BENEFITS:

1. A HIGH CONCENTRATE ORGANIC WAX & GLUE EMULSIFIER AND FLOOR CLEANER
2. DESIGNED TO WORK WITH THE ECOGUARD VCT DIAMOND ABRASIVE PADS
3. EMULSIFIES HARD, MULTIPLE COATS OF WAX, GLUE AND OTHER COATINGS
4. REMOVES DEEP , TOUGH STAINS
5. RETURNS THE ORIGINAL COLOR HUE AND BRIGHTHNESS OF A NEW FLOOR
6. 100% GREEN SOLUTION AND COMPLETELY ENVIRONMENTALLY FRIENDLY

COMPOSITION:

ECOGUARD™ VCT Clean is the combination of cleaning agents and modified organic compounds, combined with soy methyl ester in aqueous solution.

PHYSICAL PROPERTIES at 70° F (21°C):	APPROXIMATE VALUES:
Weight per Gallon:	8.52 +/- 0.10 lb./ gallon
pH:	7.0 +/- 0.2
%Solids (Concentrate):	40.0% +/- 1.0
Color:	Light Yellow
Freeze Point:	30°F (-1.1°C)
VOC (Volatile Organic Compounds) diluted:	<100 g/L (0.50 lb./gal)

Technic data sheet:

APPLICATION INSTRUCTIONS:

TEST AREA: Always test ECOGUARD VCT Clean on a small area of the surface to be treated before overall application to determine suitability and results. Use a test location that is out of the way and not in the main area of the final area.

APPLICATION: Pour Concrete Earth ECOGUARD™ VCT Clean directly onto the floor by flooding or using a low pressure high volume pump up sprayer. Spread over the surface using a foam squeegee and start using the ECOGUARD VCT Diamond Pad No. 1 fitted onto your rotary scrubbing equipment and start to abrade the floor at a forward pace gauged to allow a one to two pass removal of all wax/coatings/glue present on the surface.

COVERAGE: Approximately 2000m² / Liter in Concentration 1:250

WARNINGS:

ECOGUARD™ VCT Clean is harmful if swallowed. It is also an eye irritant and may irritate skin. Wear protective safety glasses, gloves, and clothing when handling. Avoid prolonged skin contact-wash skin with soap and water if exposed to avoid irritation. Refer to product M.S.D.S. (Material Safety Data Sheet) for further health and safety information. Keep containers closed when not in use and dispose of accordingly. Keep away from food and drink. Do not take internally. **FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.**

H.M.I.S. CODES (Hazardous Materials Identification System):

HEALTH = 1, FLAMMABILITY = 0, REACTIVITY = 0, PERSONAL PROTECTION = C

SHIPPING CLASS:

ITEM 33880, SUB 2, LTL 55 CONCRETE SEALER-WATER BASE-NOT REGULATED BY D.O.T.

PACKAGING: 1 – 5 – 25 – 120 – 500 Liter

STORAGE: 15° - 38 ° Celsius . Keep from freezing

SHELF LIFE: 2 year properly stored

Technic data sheet:

WARRANTY: isi GmbH Germany solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of isi, no other representations or statements made by isi or its representatives, in writing or orally, shall alter this warranty.

isi MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME.

If any isi product fails to conform with this warranty, isi will replace the product at no cost to Buyer.

Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. isi does not authorize anyone on its behalf to make any written or oral statements which in any way alter isi installation information or instructions in its product literature or on its packaging labels.

isi explicitly excludes any written or oral statements or implied warranty on the performance of an applied/installed product manufactured or sold by or through isi. isi has no control over isi application standards adherence, site conditions, atmospheric variations, installer/applicator skill level or the determination of the suitability of any isi products for a specific intended purpose. Buyer shall be solely responsible for determining the suitability of isi's products for the Buyer's intended purposes.

Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind.

Status 01/2017